

CHATEAU

REVOLUTION LINE

S3 SRC
38-48



Soft
WALK



OBERLEDER Eco leather

FUTTER 100% Polyester mit Bienenwabenstruktur

INNENSOHLE LIGHT & SOFT, antistatisch und atmungsaktiv

LAUFSOHLE Polyurethan

KAPPE Nicht metallische TOP COMPOSITE

ZWISCHEN-SOHLE Nicht metallische HRP INSOLE


WEITE 12

DATENBLATT

INFORMATIONEN



EINSATZGEBIETE





FTG
safety shoes

Class: S3 SRC
Sizes: 38-48
Instep: 12
Weight(±10%): 543 gr. (*)

TECHNICAL SHEET ART. CHATEAU

Description Low shoe in water-repellent Eco leather, black color, 100% polyester lining, non metallic HRP midsole, insole Light & Soft antistatic and breathable, polyurethane sole, bending resistant, abrasion resistant, oil resistant, slip resistant, antistatic, with the "little pad" SOFT WALK inside

Plus Eco leather hypoallergenic, chrome free, acid resistant, washable at 40° C, more breathable; toe protection PRO CAP

Suggested sectors of usage Chemistry/Food, building/construction, mechanical industry, naval industry

Care and Maintenance clean periodically the outsole and the upper with non aggressive substances which could compromise quality, safety and durability of the shoe, do not dry close to direct heat source



Complete shoe	Norm	Description	Unit	FTG result	EN ISO 20345 requirement
Toe cap: Top Composite toe cap, impact resistant 200 J	5.3.2.3 5.3.2.4	Impact resistance Compression resistance	mm mm	14,2 16,1	>= 14 >= 14
Midsole: non metallic HRP Insole with high tenacity fibers layers, ceramized and treated with plasma	6.2.1.1	Perforation resistance	N	1.100	>= 1.100
Antistatic footwear: the outsole is made for the dissipation of electrostatic charges	6.2.2.2	Electric resistance - Wet - Dry	Mohm Mohm	41,4 74,9	>= 0,1 <= 1000
Capacity of Energy Absorption in the heel area	6.2.4	Energy absorption in the heel area	J	37,5	>= 20
Upper: Eco leather water-repellent, black color, thickness 2,0 mm	5.4.6 5.4.3	Water vapour permeability Coefficient of permeability Tearing Strength	mg/cmq h mg/cmq N	1,8 15,0 60	>= 0,8 >= 15 >= 60
Vamp Lining: non woven textile for toe cap, grey color	5.5.3 5.5.1 5.5.2	Water vapour permeability Coefficient of permeability Tearing Strength Abrasion resistance (dry) Abrasion resistance (wet)	mg/cmq h mg/cmq N cycles cycles	3,4 30,2 30 no rupture no rupture	>= 2 >= 20 >= 15 25.600 12.800
Quarter lining: 100% honeycomb finished polyester, breathable, abrasion resistant, black colour	5.5.3 5.5.1 5.5.2	Water vapour permeability Coefficient of permeability Tearing Strength Abrasion resistance (dry) Abrasion resistance (wet)	mg/cmq h mg/cmq N cycles cycles	6,8 54,4 25 no rupture no rupture	>= 2 >= 20 >= 15 51.200 25.600
Insole lining: textile anti perforation midsole HRP Insole	5.7.3	Water Absorption Ability to release water	Mg/cm ²	78 99%	>= 70 >= 80%
Sole: polyurethane, bending resistant, abrasion resistant, oil resistant, slip resistant, antistatic, with high damping capacity thanks to the little pad SOFT WALK inserted inside	5.8.2 5.8.3 5.8.4 5.8.5 6.4.2 5.11	Tearing Strength Abrasion resistance Bending resistance Hydrolysis Hydrocarbons resistance (volume increase) Slip resistance on ceramic floor with water and detergent Slip resistance on steel floor with glycerine	KN/m mm ³ mm mm % flat inclined	5,9 154 2,5 1,0 0,2% 0,56 0,47 0,25 0,22	>= 5 <= 250 <= 4 <= 6 <= 12% >= 0,32 >= 0,28 >= 0,18 >= 0,13

Azo dye free: no presence of azo dye forbidden by normative 1907/2006/CE Attachment XVII (method UNI EN 14362-1:2004 – Textile)

(*) = Indicative weight that refers to 1/2 pair in size 42